

Cat[®] CM235

CONTINUOUS MINER

Specifications

| • | | |
|--|------------------|----------------|
| Operating Dimensions | | |
| Mining Range (recommended) | 1067-2946 mm | 42-116 in |
| Minimum Height | 914 mm | 36 in |
| Maximum Reach | 3251 mm | 10 ft 8 in |
| Ground Clearance | 229 mm | 9 in |
| Length Rear Bumper to Face | 8160 mm | 26 ft 9 in |
| Transport Dimensions | | |
| Frame Width (over rub rails) | 3277 mm | 10 ft 9 in |
| Overall Length | 11 049 mm | 36 ft 3 in |
| Height (over scrubber duct) | 914 mm | 36 in |
| Machine Weight | | |
| Weight (total) | 61.2 tonnes | 135,000 lb |
| Cutting Unit | | |
| Cutting Drum Diameter | 914 mm | 36 in |
| Cutting Drum Width | 3581 mm | 11 ft 9 in |
| Cutting Power – Motors | | |
| (one-hour rating) | 2 × 205 kW | 2 × 275 hp |
| Loading Unit | | |
| Loading Method | 6-finger CLA | |
| Conveyor Width | 965 mm | 38 in |
| Conveyor Depth | 152 mm | 6 in |
| Loading Capacity | 14-29 tonnes/min | 15-32 tons/min |
| Conveyor Power – Motors (one-hour rating) | 2 × 45 kW | 2 × 60 hp |


| Crawler Chain Width | 508 mm | 20 in |
|------------------------------------|-------------------------------------|---------------|
| Crawler Assembly Length | 2896 mm | 9 ft 6 in |
| Ground Pressure | 204 kPa | 29.6 psi |
| Crawler Speed | 0-26 m/min | 0-85 fpm |
| Traction Power – AC/VFD | | |
| (one-hour rating) | $2 \times 82 \text{ kW}$ | 2 × 110 hp |
| Pump Unit | | |
| Pump Power – Motor | | |
| (one-hour rating) | 1 × 37 kW | 1 × 50 hp |
| Optional Dust Suppression | | |
| Scrubber Assembly | Top mounted, d (bidirectional di | |
| Scrubber Type | Wet bed | |
| Scrubber Capacity | 2.8 m³/sec | 6,000 ft³/min |
| Fan Power – Motor | $1 \times 22 \text{ kW}$ | 1 × 30 hp |
| Electrical System | | |
| Machine Voltage | | |
| (International voltages available) | 950V AC 60 Hz | -17 |
| Control System | Processor base radio remote co | |
| Total Installed Power | | |
| One hour Pating without Carubbar | 701 1/1/ | 010 hp |


One-hour Rating without Scrubber 701 kW

940 hp



CM235 Continuous Miner





Dimensions (All dimensions are approximate.)

| 1 | 3581 mm | 11 ft 9 in |
|----|---------|------------|
| 2 | 76 mm | 3 in |
| 3 | 1600 mm | 63 in |
| 4 | 3277 mm | 10 ft 9 in |
| 5 | 965 mm | 38 in |
| 6 | 508 mm | 20 in |
| 7 | 914 mm | 36 in |
| 8 | 3251 mm | 10 ft 8 in |
| 9 | 914 mm | 36 in |
| 10 | 51 mm | 2 in |
| 11 | 127 mm | 5 in |
| 12 | 76 mm | 3 in |
| | | |

| 13 | 2134 mm | 7 ft 0 in | |
|----|-----------|--------------|--|
| 14 | 914 mm | 36 in | |
| 15 | 2896 mm | 9 ft 6 in | |
| 16 | 11 049 mm | 36 ft 3 in | |
| 17 | 279 mm | 11 in | |
| 18 | 229 mm | 9 in | |
| 19 | 152 mm | 6 in | |
| 20 | 2889 mm | 9 ft 5.75 in | |
| 21 | 527 mm | 1 ft 8.75 in | |
| 22 | 1683 mm | 5 ft 6.25 in | |
| 23 | 2045 in | 6 ft 8.5 in | |

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

AEHQ6873 (08-12)

© 2012 Caterpillar All Rights Reserved Printed in U.S.A.

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

